

# 屋内照明器具特性

品番 (品名)	NNN62500														
光源	LDR5L-W-E17/RF5 x1 525.0lm														
管理番号	K0169138(0)DB1														
BZ分類	BZ3/1.1/BZ4/1.4/BZ3/1.8/BZ4														

器具効率	79%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 ( X0.01)															ZCM			
下方光束	79%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	5.0	4.1	3.6	3.2	4.9	4.1	3.6	3.2	4.7	4.0	3.5	3.2	4.6	3.9	3.5	3.2	3.0		
		0.8	5.6	4.8	4.3	3.9	5.5	4.8	4.3	3.9	5.3	4.7	4.2	3.9	5.2	4.6	4.2	3.9	3.7		
		1.0	6.1	5.4	4.8	4.4	6.0	5.3	4.8	4.4	5.8	5.2	4.7	4.4	5.6	5.1	4.7	4.4	4.2		
		1.25	6.5	5.9	5.4	5.0	6.4	5.8	5.3	5.0	6.2	5.7	5.3	4.9	6.0	5.6	5.2	4.9	4.7		
下方投影面積	c m <sup>2</sup>	1.5	6.8	6.2	5.8	5.4	6.7	6.2	5.7	5.4	6.5	6.0	5.7	5.3	6.3	5.9	5.6	5.3	5.1		
		2.0	7.3	6.8	6.3	6.0	7.1	6.7	6.3	6.0	6.9	6.5	6.2	5.9	6.7	6.4	6.1	5.9	5.7		
取付高さ	器具間隔最大限		2.5	7.5	7.1	6.7	6.4	7.4	7.0	6.7	6.4	7.2	6.8	6.6	6.3	7.0	6.7	6.4	6.2	6.0	
	横方向 (A)	縦方向 (B)	3.0	7.7	7.3	7.0	6.7	7.6	7.2	6.9	6.7	7.3	7.1	6.8	6.6	7.1	6.9	6.7	6.5	6.3	
H m	0.67 H m	0.67 H m	4.0	7.9	7.6	7.3	7.1	7.8	7.5	7.3	7.1	7.6	7.3	7.1	7.0	7.4	7.2	7.0	6.9	6.7	
			5.0	8.0	7.8	7.6	7.4	7.9	7.7	7.5	7.3	7.7	7.5	7.3	7.2	7.5	7.4	7.2	7.1	6.9	
			7.0	8.2	8.0	7.8	7.7	8.0	7.9	7.7	7.6	7.8	7.7	7.6	7.5	7.7	7.6	7.4	7.3	7.1	
			10.0	8.3	8.1	8.0	7.9	8.2	8.0	7.9	7.8	8.0	7.9	7.8	7.7	7.8	7.7	7.6	7.6	7.3	

