

屋内照明器具特性

品番 (品名)	NNN71501	
光源	ONU141105LE9 ×1	1110.0 lm
管理番号	K0132246(2)DR1	
BZ分類	BZ2/0.7/BZ1/0.9/BZ2	

器具効率	96%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	室指数	床	10%				10%				10%				10%				0%
下方光束	96%		照明率 (×0.01)																ZCM	
保守率	良 中 否	0.81	0.6	68	60	54	51	67	59	54	51	66	59	54	50	64	58	53	50	49
		0.77	0.8	77	69	64	60	76	69	64	60	74	68	63	60	72	67	63	59	58
		0.68	1.0	82	75	70	66	81	74	70	66	79	73	69	66	77	72	68	66	64
			1.25	86	80	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69
下方投影面積	c m ²	1.5	89	84	80	76	88	83	79	76	86	82	78	75	84	80	77	75	73	
		2.0	93	88	85	82	92	88	84	81	89	86	83	81	87	84	82	80	78	
取付高さ	器具間隔最大限		2.5	95	91	88	85	94	90	87	85	92	89	86	84	89	87	85	83	
	横方向 (A)	縦方向 (B)	3.0	97	93	91	88	95	92	90	88	93	91	88	86	91	89	87	85	
H m	0.76 H m	0.76 H m	4.0	98	96	94	92	97	95	93	91	95	93	91	90	93	91	90	88	
			5.0	100	97	96	94	98	96	95	93	96	95	93	92	94	93	91	90	
			7.0	101	99	98	97	100	98	97	96	97	96	95	94	95	94	93	90	
			10.0	102	101	100	99	101	100	99	98	98	98	97	96	96	95	94	92	

