

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 3
光源	NNU140115KLE9 ×1 1020.0 l m
管理番号	K0190828 (0) DB 1
B Z 分類	B Z 2

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		94 %																						
保守率		良 中 否	0.81	0.6	63	54	48	44	62	53	48	44	60	52	47	43	58	52	47	43	42			
			0.77	0.8	72	64	59	54	71	64	58	54	69	63	58	54	67	62	57	54	52			
			0.68	1.0	78	71	66	62	77	70	65	62	75	69	65	61	73	68	64	61	59			
				1.25	83	77	72	68	82	76	72	68	80	75	71	68	78	73	70	67	65			
下方投影面積		cm ²	1.5	86	80	76	73	85	80	76	72	83	78	75	72	81	77	74	71	69				
等価発光面積			cm ²	2.0	90	86	82	79	89	85	81	78	87	83	80	77	85	82	79	77	75			
取付 高さ	器具間隔最大限		2.5	92	89	85	83	91	88	85	82	89	86	83	81	87	84	82	80	78				
	横方向 (A) 縦方向 (B)		3.0	94	91	88	85	93	90	87	85	91	88	86	84	88	86	84	83	81				
H m	1.15 H m	1.15 H m	4.0	96	93	91	89	95	92	90	88	93	91	89	87	90	89	87	86	84				
			5.0	97	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	86				
			7.0	98	97	95	94	97	96	95	93	95	94	93	92	93	92	91	90	88				
			10.0	99	98	97	96	98	97	96	95	96	95	94	94	94	93	93	92	89				

