

屋内照明器具特性

品番 (品名)	NNN71503														
光源	NNU240105LE9 ×1 2050.0 lm														
管理番号	K0133659(0)DR1														
BZ分類	BZ2														

器具効率	97%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	97%																			
保守率	良 中 否	0.81	0.6	64	55	49	44	63	54	48	44	61	53	48	44	60	52	48	44	42
		0.77	0.8	74	65	59	55	73	65	59	55	71	64	59	55	69	63	58	55	53
			1.0	80	72	67	63	79	72	66	62	77	70	66	62	75	69	65	62	60
		0.68	1.25	85	78	73	69	84	78	73	69	82	76	72	69	79	75	71	68	66
下方投影面積	c m ²	1.5	88	82	78	74	87	82	77	74	85	80	76	73	83	79	75	72	71	
		2.0	93	88	84	80	91	87	83	80	89	85	82	79	87	83	81	78	76	
取付高さ	器具間隔最大限		2.5	95	91	87	85	94	90	87	84	91	88	85	83	89	87	84	82	80
	横方向 (A)	縦方向 (B)	3.0	97	93	90	87	95	92	89	87	93	90	88	86	91	89	87	85	83
H m	1.12 H m	1.12 H m	4.0	99	96	94	91	98	95	93	91	95	93	91	89	93	91	90	88	86
			5.0	100	98	96	94	99	97	95	93	96	95	93	92	94	93	92	90	88
			7.0	101	100	98	97	100	99	97	96	98	97	95	94	96	95	94	93	90
			10.0	102	101	100	99	101	100	99	98	99	98	97	96	97	96	95	95	92

