

屋内照明器具特性

品番 (品名)	NNN71503									
光源	NNU240105KLE9 x1					2050.0 lm				
管理番号	K0190819(0)DB1									
BZ分類	BZ2									

器具効率	95%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	95%																			
保守率	良 中 否	0.81	0.6	64	55	49	44	63	54	48	44	61	53	48	44	59	52	48	44	43
		0.77	0.8	73	65	59	55	72	65	59	55	70	63	59	55	68	62	58	55	53
		0.68	1.0	79	72	67	63	78	71	66	63	76	70	66	62	74	69	65	62	60
			1.25	84	78	73	69	83	77	72	69	81	76	72	68	79	74	71	68	66
下方投影面積	c m ²	1.5	87	82	77	74	86	81	77	73	84	79	76	73	82	78	75	72	70	
		2.0	91	87	83	80	90	86	82	79	88	84	81	78	86	83	80	78	76	
取付高さ	器具間隔最大限		2.5	94	90	86	84	92	89	86	83	90	87	84	82	88	85	83	81	79
	横方向 (A)	縦方向 (B)	3.0	95	92	89	86	94	91	88	86	92	89	87	85	90	87	85	84	82
H m	1.13 H m	1.13 H m	4.0	97	95	92	90	96	94	91	89	94	92	90	88	92	90	88	87	85
			5.0	98	96	94	92	97	95	93	92	95	93	92	90	93	91	90	89	87
			7.0	100	98	97	95	98	97	96	94	96	95	94	93	94	93	92	91	89
			10.0	101	99	98	97	99	98	97	97	97	96	96	95	95	94	94	93	91

