

屋内照明器具特性

品番 (品名)	NNN71503	
光源	ONU240115KLE9 x1	1840.0 lm
管理番号	K0190820(0)DB1	
BZ分類	BZ2	

器具効率	95%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.81 0.77 0.68	0.6	64	55	49	44	63	54	48	44	61	53	48	44	59	52	48	44	43	
		0.8	74	65	60	55	72	65	59	55	70	64	59	55	68	63	58	55	53	
		1.0	80	72	67	63	78	72	67	63	76	70	66	62	74	69	65	62	60	
		1.25	84	78	73	69	83	77	73	69	81	76	72	69	79	75	71	68	66	
下方投影面積	c m ²	1.5	87	82	77	74	86	81	77	73	84	79	76	73	82	78	75	72	70	
		2.0	91	87	83	80	90	86	82	79	88	84	81	79	86	83	80	78	76	
取付高さ	器具間隔最大限		2.5	94	90	87	84	93	89	86	83	90	87	85	82	88	86	83	79	
	横方向 (A)	縦方向 (B)	3.0	95	92	89	87	94	91	88	86	92	89	87	85	90	88	86	84	82
H m	1.15 H m	1.15 H m	4.0	97	95	92	90	96	94	92	90	94	92	90	88	92	90	89	87	85
			5.0	99	96	94	93	97	95	94	92	95	93	92	91	93	92	90	89	87
			7.0	100	98	97	95	99	97	96	95	96	95	94	93	94	93	92	89	
			10.0	101	100	99	98	100	99	98	97	97	97	96	95	95	94	93	91	

