

屋内照明器具特性

品番 (品名)	NNN1 2 6 2 1 B	
光源	LDT6L - G / S / T6 ×1	810.0 lm
管理番号	K0163079 (0) DB 1	
BZ分類	BZ10	

器具効率	67 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		32 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	35 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	2.8	1.9	1.4	1.0	2.6	1.8	1.3	0.9	2.1	1.4	1.0	0.7	1.6	1.1	0.8	0.5	0.2
	中	0.6	0.8	3.4	2.5	1.9	1.4	3.0	2.3	1.7	1.3	2.5	1.8	1.4	1.1	1.9	1.5	1.1	0.8	0.4
	否	0.56	1.0	3.7	2.9	2.3	1.8	3.4	2.6	2.1	1.7	2.8	2.2	1.7	1.4	2.2	1.7	1.3	1.1	0.5
下方投影面積	等価発光面積	cm ²	1.25	4.1	3.3	2.7	2.2	3.7	3.0	2.5	2.0	3.0	2.5	2.0	1.7	2.4	2.0	1.6	1.3	0.7
			1.5	4.4	3.6	3.0	2.6	4.0	3.3	2.8	2.4	3.3	2.7	2.3	2.0	2.6	2.2	1.8	1.6	0.9
取付高さ	器具間隔最大限		2.0	4.8	4.1	3.6	3.1	4.4	3.8	3.3	2.9	3.6	3.1	2.7	2.4	2.9	2.5	2.2	1.9	1.2
	横方向 (A)	縦方向 (B)	2.5	5.0	4.4	3.9	3.5	4.6	4.1	3.6	3.2	3.8	3.4	3.0	2.7	3.1	2.8	2.5	2.2	1.4
Hm	0.00Hm	0.00Hm	3.0	5.2	4.7	4.2	3.8	4.8	4.3	3.9	3.5	4.0	3.6	3.3	3.0	3.3	3.0	2.7	2.4	1.6
			4.0	5.5	5.0	4.6	4.3	5.1	4.7	4.3	4.0	4.2	3.9	3.6	3.4	3.5	3.2	3.0	2.8	2.8
			5.0	5.7	5.3	4.9	4.6	5.2	4.9	4.5	4.3	4.4	4.1	3.9	3.6	3.6	3.4	3.2	3.0	2.1
			7.0	5.9	5.5	5.3	5.0	5.4	5.1	4.9	4.6	4.6	4.4	4.2	4.0	3.8	3.6	3.5	3.3	2.3
			10.0	6.0	5.8	5.6	5.3	5.6	5.4	5.2	5.0	4.8	4.6	4.4	4.3	4.0	3.8	3.7	3.6	2.6

