

# 屋内照明器具特性

品番 (品名)	NNN62500				
光源	LDA6L-E17/D ×1                      370.0 lm				
管理番号	K0137732(0)DB1				
BZ分類	BZ1/1.8/BZ2				

器具効率	47%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	47%	室指数	照明率 (×0.01)																				ZCM
保守率	良 中 否	0.67	0.6	3.5	3.1	2.8	2.7	3.4	3.1	2.8	2.7	3.4	3.0	2.8	2.7	3.3	3.0	2.8	2.7	2.6			
		0.63	0.8	3.8	3.5	3.2	3.1	3.8	3.5	3.2	3.1	3.7	3.4	3.2	3.1	3.6	3.4	3.2	3.0	3.0			
		0.56	1.0	4.1	3.8	3.5	3.3	4.0	3.7	3.5	3.3	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.3	3.2			
			1.25	4.3	4.0	3.8	3.6	4.2	4.0	3.7	3.6	4.1	3.9	3.7	3.6	4.0	3.8	3.7	3.5	3.5			
下方投影面積	c m <sup>2</sup>	1.5	4.4	4.1	3.9	3.8	4.3	4.1	3.9	3.8	4.2	4.0	3.9	3.7	4.1	4.0	3.8	3.7	3.6				
		2.0	4.6	4.4	4.2	4.0	4.5	4.3	4.2	4.0	4.4	4.2	4.1	4.0	4.3	4.2	4.0	3.9	3.9				
取付高さ	器具間隔最大限		2.5	4.7	4.5	4.3	4.2	4.6	4.5	4.3	4.2	4.5	4.4	4.2	4.1	4.4	4.3	4.2	4.1				
	横方向 (A)	縦方向 (B)	3.0	4.7	4.6	4.5	4.3	4.7	4.5	4.4	4.3	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.2				
H m	1.09 H m	1.09 H m	4.0	4.8	4.7	4.6	4.5	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.2				
			5.0	4.9	4.8	4.7	4.6	4.8	4.7	4.7	4.6	4.7	4.6	4.6	4.5	4.6	4.6	4.5	4.4				
			7.0	5.0	4.9	4.8	4.7	4.9	4.8	4.8	4.7	4.8	4.7	4.7	4.6	4.7	4.6	4.6	4.5				
			10.0	5.0	4.9	4.9	4.8	4.9	4.9	4.8	4.8	4.8	4.8	4.8	4.7	4.7	4.7	4.7	4.6				

