

屋内照明器具特性

品番 (品名)	NNN62500															
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1 m															
管理番号	K0169145(0)DB1															
BZ分類	BZ2															

器具効率	49%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	0% 49%	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.67 0.63 0.56	0.6	3.4	3.0	2.7	2.5	3.4	3.0	2.7	2.5	3.3	2.9	2.7	2.5	3.2	2.9	2.6	2.5	2.4	
		0.8	3.8	3.4	3.2	3.0	3.8	3.4	3.1	2.9	3.7	3.4	3.1	2.9	3.6	3.3	3.1	2.9	2.8	
		1.0	4.1	3.7	3.5	3.3	4.1	3.7	3.5	3.3	3.9	3.6	3.4	3.3	3.8	3.6	3.4	3.2	3.2	
		1.25	4.3	4.0	3.8	3.6	4.3	4.0	3.7	3.6	4.2	3.9	3.7	3.5	4.1	3.8	3.7	3.5	3.4	
下方投影面積 等価発光面積	c m ² c m ²	1.5	4.5	4.2	4.0	3.8	4.4	4.2	3.9	3.8	4.3	4.1	3.9	3.7	4.2	4.0	3.8	3.7	3.6	
		2.0	4.7	4.4	4.2	4.1	4.6	4.4	4.2	4.1	4.5	4.3	4.2	4.0	4.4	4.2	4.1	4.0	3.9	
取付 高さ	器具間隔最大限		2.5	4.8	4.6	4.4	4.3	4.7	4.6	4.4	4.3	4.6	4.5	4.3	4.2	4.5	4.4	4.3	4.2	
	横方向 (A) 縦方向 (B)	3.0	4.9	4.7	4.6	4.4	4.8	4.7	4.5	4.4	4.7	4.6	4.5	4.3	4.6	4.5	4.4	4.3	4.2	
H m	1.06 H m	1.06 H m	4.0	5.0	4.9	4.7	4.6	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.3	
			5.0	5.1	4.9	4.8	4.7	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.4	
			7.0	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.9	4.9	4.8	4.8	4.8	4.8	4.7	4.7	4.6	
			10.0	5.2	5.1	5.1	5.0	5.1	5.1	5.0	5.0	5.0	4.9	4.9	4.9	4.9	4.8	4.8	4.6	

