

# 屋内照明器具特性

品番 (品名)	LGB80581									
光源	LED2700_70_130 x1					130.0 lm				
管理番号	K0147468(0)DB1									
BZ分類	BZ5/0.7/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		50%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		50%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m <sup>2</sup>		1.25	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	
	等価発光面積		c m <sup>2</sup>	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	
	横方向 (A)	縦方向 (B)	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	
H <sub>m</sub>	0.65H <sub>m</sub>	1.49H <sub>m</sub>	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	
			5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0	
			7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0	
			10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0	

