

屋内照明器具特性

品番 (品名)	NNFJ 2 1 3 1 1									
光源	LED5000_85_1150 x1 1150.0 lm									
管理番号	K0144558 (2) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	8 %																			
下方光束	92 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.83 中 0.81 否 0.77	0.6	55	43	35	29	53	42	34	29	50	40	33	29	47	39	32	28	26	
		0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	34	
		1.0	71	60	52	46	69	59	51	46	65	56	50	45	61	54	48	44	41	
		1.25	77	67	59	54	75	65	58	53	70	63	57	52	67	60	55	50	47	
下方投影面積	c m ²	1.5	81	72	65	59	79	70	64	58	74	67	61	57	70	64	59	55	52	
		2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	66	63	59	
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	83	78	74	70	79	75	71	68	64
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	90	85	80	76	86	81	77	74	82	78	75	71	67
1.5m	1.93 m	1.9 m	4.0	96	91	87	83	93	89	85	81	89	85	82	79	85	82	79	77	72
2	2.57	2.5	5.0	98	94	90	87	95	92	88	85	91	88	85	83	87	85	82	80	75
2.5	3.21	3.1	7.0	100	97	94	91	98	95	92	90	94	91	89	87	90	88	86	84	79
3	3.84	3.68	10.0	102	100	97	95	100	98	96	94	96	94	92	90	92	90	89	87	83

