

# 屋内照明器具特性

品番 (品名)	NND26150K														
光源	LEDRED_90_118.7 x1 118.7 lm														
管理番号	K0147723(0)DD1														
BZ分類	BZ3/1.4/BZ4/6.0/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		18%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		82%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 ) ZCM																				
保守率	良	0.88	0.6	60	49	42	38	58	48	42	37	54	46	40	36	50	43	39	35	32	
	中	0.86	0.8	69	59	52	47	66	57	51	46	62	54	49	45	58	51	47	43	39	
	否	0.81	1.0	74	65	58	53	72	63	57	52	67	60	55	51	62	57	52	49	45	
			1.25	79	71	65	60	77	69	63	59	71	65	60	56	67	61	57	54	50	
下方投影面積 等価発光面積			cm <sup>2</sup>	1.5	83	75	69	64	80	73	68	63	75	69	64	60	70	65	61	58	53
			cm <sup>2</sup>	2.0	88	81	76	71	85	79	74	70	79	74	70	67	74	70	66	64	58
				2.5	91	85	80	76	88	82	78	74	82	78	74	71	76	73	70	67	62
取付高さ	器具間隔最大限			3.0	93	88	83	80	90	85	81	78	84	80	77	74	78	75	73	70	64
	H <sub>m</sub>	1.01H <sub>m</sub>	0.91H <sub>m</sub>	4.0	95	91	88	85	92	89	85	82	86	83	81	78	81	78	76	74	67
				5.0	97	94	90	88	94	91	88	85	88	85	83	81	82	80	78	77	70
				7.0	99	96	94	92	96	93	91	89	90	88	86	84	84	82	81	80	72
				10.0	100	98	97	95	97	95	94	92	91	90	88	87	85	84	83	82	75

