

屋内照明器具特性

品番 (品名)	LGB52623	
光源	LED2700_70_1430 x1	1430.0 lm
管理番号	K0147587(0)DB1	
BZ分類	BZ6/0.7/BZ5/2.8/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 9%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 91%	室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否 0.63 0.6 0.56	0.6	53	41	33	27	51	40	32	27	48	38	31	26	45	36	30	26	23		
		0.8	63	51	42	36	61	49	42	36	57	47	40	35	53	45	39	34	31		
		1.0	69	58	49	43	67	56	49	43	63	54	47	42	59	51	45	40	37		
		1.25	75	64	56	50	72	63	55	50	68	60	53	48	64	57	51	47	43		
下方投影面積 等価発光面積	c m ²	1.5	79	69	62	56	77	68	60	55	72	64	58	53	68	61	56	52	48		
		2.0	85	76	69	64	82	74	68	63	77	71	65	61	73	68	63	59	55		
取付 高さ	器具間隔最大限		2.5	88	81	75	69	86	79	73	68	81	75	70	66	76	72	68	64	60	
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	79	75	71	68	63	
H m	1.29 H m	1.29 H m	4.0	94	89	84	80	92	87	82	78	87	83	79	76	82	79	76	73	68	
			5.0	96	92	88	84	94	90	86	82	89	86	82	79	85	82	79	77	72	
			7.0	99	95	92	89	96	93	90	87	92	89	87	84	87	85	83	81	76	
			10.0	101	98	96	93	98	96	94	92	94	92	90	88	90	88	86	85	80	

