

屋内照明器具特性

品番 (品名)	LGB51617									
光源	LED2700_70_820 x1					820.0 lm				
管理番号	K0147632(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		20%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		80%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	75	65	58	52	72	63	56	51	66	58	53	48	60	54	50	46	41	
	等価発光面積		c m ²	1.5	79	70	63	57	76	67	61	56	69	63	57	53	64	58	54	50	45
取付高さ	器具間隔最大限		2.5	88	81	76	71	84	78	73	69	78	73	69	65	72	68	64	61	55	
	横方向 (A)	縦方向 (B)	3.0	90	84	79	75	87	82	77	73	80	76	72	69	74	71	68	65	58	
H m	1.29 H m	1.29 H m	4.0	93	89	85	81	90	86	82	79	83	80	77	74	77	74	72	70	62	
			5.0	95	91	88	85	92	88	85	82	85	82	80	77	79	77	75	73	65	
			7.0	98	95	92	89	94	91	89	87	87	85	83	81	81	79	78	76	68	
			10.0	99	97	95	93	96	94	92	90	89	88	86	85	83	82	80	79	71	

