

屋内照明器具特性

品番 (品名)	NNN61522B				
光源	LDA4L-G/K4	x1	485.0 lm		
管理番号	K0178364(0)DB1				
BZ分類	BZ3/0.7/BZ2				

器具効率	36%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	36%																																																						
保守率	良 中 否	0.67	0.6	2.4	2.0	1.8	1.6	2.3	2.0	1.8	1.6	2.3	2.0	1.7	1.6	2.2	1.9	1.7	1.6	1.5																																			
		0.63	0.8	2.7	2.4	2.2	2.0	2.7	2.4	2.2	2.0	2.6	2.3	2.2	2.0	2.5	2.3	2.1	2.0	1.9																																			
		0.56	1.0	3.0	2.7	2.5	2.3	2.9	2.7	2.5	2.3	2.8	2.6	2.4	2.3	2.8	2.6	2.4	2.3	2.2																																			
			1.25	3.2	2.9	2.7	2.6	3.1	2.9	2.7	2.6	3.0	2.8	2.7	2.5	3.0	2.8	2.6	2.5	2.5																																			
下方投影面積	c m ²	1.5	3.3	3.1	2.9	2.8	3.3	3.0	2.9	2.7	3.2	3.0	2.8	2.7	3.1	2.9	2.8	2.7	2.6																																				
		2.0	3.5	3.3	3.1	3.0	3.4	3.2	3.1	3.0	3.3	3.2	3.1	3.0	3.2	3.1	3.0	2.9	2.9																																				
取付高さ	器具間隔最大限		2.5	3.6	3.4	3.3	3.2	3.5	3.4	3.2	3.1	3.4	3.3	3.2	3.1	3.3	3.2	3.1	3.0																																				
	横方向 (A)	縦方向 (B)	3.0	3.6	3.5	3.4	3.3	3.6	3.5	3.3	3.3	3.5	3.4	3.3	3.2	3.4	3.3	3.2	3.1																																				
H _m	1.22H _m	1.22H _m	4.0	3.7	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.3	3.5	3.4	3.4	3.3																																				
			5.0	3.7	3.7	3.6	3.5	3.7	3.6	3.6	3.5	3.6	3.5	3.5	3.4	3.5	3.5	3.4	3.3																																				
			7.0	3.8	3.7	3.7	3.6	3.7	3.7	3.6	3.6	3.7	3.6	3.6	3.5	3.6	3.5	3.5	3.4																																				
			10.0	3.8	3.8	3.7	3.7	3.8	3.7	3.7	3.7	3.7	3.7	3.6	3.6	3.6	3.6	3.6	3.5																																				

