

屋内照明器具特性

品番 (品名)	NNN61523W									
光源	LDA4L-H/S/4 ×1					485.0 lm				
管理番号	K0178374(0)DB1									
BZ分類	BZ3									

器具効率	64%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	64%																																																						
保守率	良 中 否	0.67	0.6	41	34	30	27	40	34	30	27	39	33	29	27	38	33	29	27	26																																			
		0.63	0.8	48	41	37	34	47	41	37	34	45	40	36	34	44	39	36	34	32																																			
		0.56	1.0	52	46	42	39	51	46	42	39	49	45	41	39	48	44	41	38	37																																			
			1.25	55	50	46	43	54	50	46	43	53	49	45	43	51	48	45	43	41																																			
下方投影面積	c m ²	1.5	57	53	49	47	56	52	49	46	55	51	48	46	53	50	48	46	44																																				
		2.0	60	57	54	51	59	56	53	51	58	55	52	50	56	54	52	50	49																																				
取付高さ	器具間隔最大限		2.5	62	59	56	54	61	58	56	54	60	57	55	53	58	56	54	53	51																																			
	横方向 (A)	縦方向 (B)	3.0	63	61	58	56	63	60	58	56	61	59	57	55	59	58	56	55	53																																			
H m	1.28 H m	1.28 H m	4.0	65	63	61	59	64	62	60	59	62	61	59	58	61	60	58	57	56																																			
			5.0	66	64	63	61	65	63	62	61	63	62	61	60	62	61	60	59	57																																			
			7.0	67	66	64	63	66	65	64	63	65	64	63	62	63	62	61	61	59																																			
			10.0	68	67	66	65	67	66	65	65	65	65	64	63	64	63	63	62	60																																			

