

屋内照明器具特性

品番 (品名)	NNN61523B														
光源	LDA7L-H/S/6 ×1 810.0 lm														
管理番号	K0178369(0)DB1														
BZ分類	BZ1														

器具効率	35%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	35%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	2.5	2.2	2.0	1.9	2.5	2.2	2.0	1.9	2.4	2.2	2.0	1.9	2.4	2.1	2.0	1.9	1.8		
		0.8	2.8	2.6	2.4	2.3	2.8	2.5	2.4	2.3	2.7	2.5	2.4	2.2	2.7	2.5	2.3	2.2	2.2		
		1.0	3.0	2.8	2.6	2.5	3.0	2.8	2.6	2.5	2.9	2.7	2.6	2.5	2.9	2.7	2.6	2.5	2.4		
		1.25	3.2	3.0	2.8	2.7	3.1	3.0	2.8	2.7	3.1	2.9	2.8	2.7	3.0	2.9	2.8	2.7	2.6		
下方投影面積 等価発光面積	c m ² c m ²	1.5	3.3	3.1	3.0	2.9	3.2	3.1	2.9	2.8	3.2	3.0	2.9	2.8	3.1	3.0	2.9	2.8	2.7		
		2.0	3.4	3.3	3.1	3.0	3.4	3.2	3.1	3.0	3.3	3.2	3.1	3.0	3.2	3.1	3.0	3.0	2.9		
		2.5	3.5	3.4	3.3	3.2	3.4	3.3	3.2	3.2	3.4	3.3	3.2	3.1	3.3	3.2	3.1	3.1	3.0		
取付高さ	器具間隔最大限		3.0	3.5	3.4	3.3	3.3	3.5	3.4	3.3	3.2	3.4	3.3	3.3	3.2	3.3	3.3	3.2	3.1		
	横方向 (A)	縦方向 (B)																			
H m	1.17 H m	1.17 H m	4.0	3.6	3.5	3.4	3.4	3.5	3.5	3.4	3.3	3.5	3.4	3.3	3.3	3.4	3.3	3.3	3.2	3.2	
			5.0	3.6	3.5	3.5	3.4	3.6	3.5	3.5	3.4	3.5	3.4	3.4	3.4	3.4	3.4	3.3	3.3	3.2	
			7.0	3.6	3.6	3.6	3.5	3.6	3.6	3.5	3.5	3.5	3.5	3.5	3.5	3.4	3.5	3.4	3.4	3.4	3.3
			10.0	3.7	3.6	3.6	3.6	3.6	3.6	3.6	3.5	3.6	3.5	3.5	3.5	3.5	3.5	3.4	3.4	3.4	3.3

