

屋内照明器具特性

品番 (品名)	LSEB2058	
光源	LED3500_70_430 ×1	430.0 l m
管理番号	K0141819 (0) DB 1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	4 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	96 %		室指数	照明率 (X0.01)																ZCM
保守率	良	0.63	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.2	4.2	3.5	3.0	4.9	4.1	3.4	3.0	2.8
	中	0.6	0.8	6.6	5.5	4.7	4.1	6.4	5.4	4.6	4.1	6.1	5.2	4.5	4.0	5.8	5.0	4.4	4.0	3.7
	否	0.56	1.0	7.3	6.2	5.4	4.9	7.1	6.1	5.4	4.8	6.7	5.9	5.3	4.8	6.4	5.7	5.1	4.7	4.4
			1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.6	7.3	6.6	6.0	5.5	7.0	6.3	5.8	5.4	5.1
下方投影面積			1.5	8.3	7.4	6.7	6.2	8.1	7.3	6.6	6.1	7.7	7.0	6.5	6.0	7.4	6.8	6.3	5.9	5.6
等価発光面積			2.0	8.8	8.1	7.5	7.0	8.6	8.0	7.4	6.9	8.3	7.7	7.2	6.8	7.9	7.4	7.0	6.7	6.3
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.0	7.6	9.0	8.4	7.9	7.5	8.6	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.8
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.9	8.4	8.1	7.7	8.5	8.2	7.8	7.6	7.2
Hm	1.26Hm	1.26Hm	4.0	9.7	9.3	8.9	8.6	9.6	9.1	8.8	8.5	9.2	8.9	8.5	8.3	8.9	8.6	8.3	8.1	7.7
			5.0	9.9	9.6	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.1	8.8	8.6	8.4	8.0
			7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.6	9.4	9.2	9.0	9.3	9.1	9.0	8.8	8.4
			10.0	10.3	10.1	9.9	9.7	10.1	10.0	9.8	9.6	9.8	9.7	9.5	9.4	9.5	9.4	9.2	9.1	8.7

