

屋内照明器具特性	
品番 (品名)	FYY26150
光源	LED5000_85_2520 x1 2520.0 lm
管理番号	K0149006(0)DB1
BZ分類	BZ4

器具効率	94%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.83 中 0.81 否 0.77	0.6	56	45	38	33	55	44	37	33	52	43	37	32	50	42	36	32	31	
		0.8	65	55	48	43	64	55	48	43	62	53	47	43	59	52	47	43	41	
		1.0	72	62	56	51	70	62	55	50	68	60	54	50	65	59	54	50	48	
		1.25	77	69	63	58	76	68	62	57	73	66	61	57	71	65	60	57	55	
下方投影面積	cm ²	1.5	81	74	68	63	80	73	67	63	77	71	66	62	74	69	65	61	59	
		2.0	86	80	75	70	85	79	74	70	82	77	73	69	79	75	72	69	66	
取付高さ	器具間隔最大限		2.5	89	84	79	76	88	83	79	75	85	81	77	74	83	79	76	73	71
	横方向 (A)	縦方向 (B)	3.0	91	87	83	79	90	86	82	79	87	84	81	78	85	82	79	77	74
1.5m	1.96m	2.25m	4.0	94	90	87	84	93	89	86	84	90	87	85	82	88	85	83	81	79
2	2.61	2.9	5.0	96	93	90	88	94	92	89	87	92	90	87	85	90	88	86	84	82
2.5	3.26	3.57	7.0	98	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	85
3	3.9	4.25	10.0	99	97	96	94	98	96	95	94	95	94	93	92	93	92	91	90	88

