

# 屋内照明器具特性

品番 (品名)	FYY26100										
光源	LED3500_85_2270 x1 2270.0 1m										
管理番号	K0149006(0)DB1										
BZ分類	BZ4										

器具効率	94%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	94%		室指数	照明率 ( X0.01 )																ZCM
保守率	良	0.83	0.6	5.6	4.5	3.8	3.3	5.5	4.4	3.7	3.3	5.2	4.3	3.7	3.2	5.0	4.2	3.6	3.2	3.1
	中	0.81	0.8	6.5	5.5	4.8	4.3	6.4	5.5	4.8	4.3	6.2	5.3	4.7	4.3	5.9	5.2	4.7	4.3	4.1
	否	0.77	1.0	7.2	6.2	5.6	5.1	7.0	6.2	5.5	5.0	6.8	6.0	5.4	5.0	6.5	5.9	5.4	5.0	4.8
			1.25	7.7	6.9	6.3	5.8	7.6	6.8	6.2	5.7	7.3	6.6	6.1	5.7	7.1	6.5	6.0	5.7	5.5
下方投影面積			1.5	8.1	7.4	6.8	6.3	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	7.4	6.9	6.5	6.1	5.9
等価発光面積			2.0	8.6	8.0	7.5	7.0	8.5	7.9	7.4	7.0	8.2	7.7	7.3	6.9	7.9	7.5	7.2	6.9	6.6
取付高さ	器具間隔最大限		2.5	8.9	8.4	7.9	7.6	8.8	8.3	7.9	7.5	8.5	8.1	7.7	7.4	8.3	7.9	7.6	7.3	7.1
	横方向 (A)	縦方向 (B)	3.0	9.1	8.7	8.3	7.9	9.0	8.6	8.2	7.9	8.7	8.4	8.1	7.8	8.5	8.2	7.9	7.7	7.4
1.5m	1.96m	2.25m	4.0	9.4	9.0	8.7	8.4	9.3	8.9	8.6	8.4	9.0	8.7	8.5	8.2	8.8	8.5	8.3	8.1	7.9
2	2.61	2.9	5.0	9.6	9.3	9.0	8.8	9.4	9.2	8.9	8.7	9.2	9.0	8.7	8.5	9.0	8.8	8.6	8.4	8.2
2.5	3.26	3.57	7.0	9.8	9.5	9.3	9.1	9.6	9.4	9.2	9.1	9.4	9.2	9.1	8.9	9.2	9.0	8.9	8.8	8.5
3	3.9	4.25	10.0	9.9	9.7	9.6	9.4	9.8	9.6	9.5	9.4	9.5	9.4	9.3	9.2	9.3	9.2	9.1	9.0	8.8

