

屋内照明器具特性

| | | |
|---------|----------------|----------|
| 品番 (品名) | NNN61513WK | |
| 光源 | LDA7L-H/S/6 ×1 | 810.0 lm |
| 管理番号 | K0178353(0)DB1 | |
| BZ分類 | BZ3 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-----------------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率 | 72% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 0% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 72% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 46 | 39 | 34 | 30 | 45 | 38 | 33 | 30 | 44 | 37 | 33 | 30 | 42 | 37 | 33 | 30 | 29 | |
| | 中 | 0.63 | 0.8 | 54 | 47 | 42 | 38 | 53 | 46 | 42 | 38 | 51 | 45 | 41 | 38 | 49 | 44 | 41 | 38 | 37 | |
| | 否 | 0.56 | 1.0 | 58 | 52 | 47 | 44 | 57 | 51 | 47 | 44 | 55 | 50 | 47 | 44 | 54 | 49 | 46 | 43 | 42 | |
| | | | 1.25 | 62 | 56 | 52 | 49 | 61 | 56 | 52 | 49 | 59 | 55 | 51 | 49 | 57 | 54 | 51 | 48 | 47 | |
| 下方投影面積 | cm ² | | 1.5 | 65 | 60 | 56 | 53 | 64 | 59 | 55 | 52 | 62 | 58 | 55 | 52 | 60 | 57 | 54 | 52 | 50 | |
| | 等価発光面積 | | cm ² | 2.0 | 68 | 64 | 61 | 58 | 67 | 63 | 60 | 58 | 65 | 62 | 59 | 57 | 63 | 61 | 58 | 56 | 55 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 70 | 67 | 64 | 61 | 69 | 66 | 63 | 61 | 67 | 65 | 62 | 60 | 65 | 63 | 61 | 59 | 58 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 71 | 68 | 66 | 64 | 70 | 68 | 65 | 63 | 69 | 66 | 64 | 62 | 67 | 65 | 63 | 62 | 60 | |
| Hm | 1.25Hm | 1.25Hm | 4.0 | 73 | 71 | 69 | 67 | 72 | 70 | 68 | 66 | 70 | 69 | 67 | 65 | 69 | 67 | 66 | 65 | 63 | |
| | | | 5.0 | 74 | 72 | 71 | 69 | 73 | 72 | 70 | 68 | 72 | 70 | 69 | 67 | 70 | 69 | 67 | 66 | 64 | |
| | | | 7.0 | 75 | 74 | 73 | 71 | 75 | 73 | 72 | 71 | 73 | 72 | 71 | 70 | 71 | 70 | 69 | 69 | 67 | |
| | | | 10.0 | 76 | 75 | 74 | 73 | 75 | 74 | 74 | 73 | 74 | 73 | 72 | 71 | 72 | 71 | 71 | 70 | 68 | |

