

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 2 WK
光源	LDA4 L - G / K4 ×1 485.0 lm
管理番号	K0178352 (0) DB 1
B Z 分類	BZ3

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	39	32	28	25	38	32	28	25	37	31	28	25	36	31	27	25	24
			0.63	0.8	45	39	35	32	45	39	35	32	43	38	34	32	42	37	34	32	30
			0.56	1.0	49	44	40	37	48	43	40	37	47	42	39	36	45	42	39	36	35
				1.25	53	48	44	41	52	47	44	41	50	46	43	41	49	45	43	40	39
下方投影面積 等価発光面積		c m ²		1.5	55	51	47	44	54	50	47	44	52	49	46	44	51	48	45	43	42
				2.0	58	54	51	49	57	54	51	49	55	53	50	48	54	52	49	48	46
				2.5	60	57	54	52	59	56	54	52	57	55	53	51	56	54	52	50	49
				3.0	61	58	56	54	60	58	56	54	59	56	55	53	57	55	54	52	51
H m	1.25 H m	1.25 H m		4.0	63	61	59	57	62	60	58	57	60	59	57	56	59	57	56	55	53
				5.0	64	62	60	59	63	61	60	58	61	60	59	57	60	59	58	57	55
				7.0	65	63	62	61	64	63	62	61	62	61	60	59	61	60	59	58	57
				10.0	65	64	64	63	65	64	63	62	63	62	62	61	62	61	61	60	58

