

| 屋内照明器具特性 |                                     |
|----------|-------------------------------------|
| 品番 (品名)  | NNN6 1 5 1 2 WK                     |
| 光源       | LDA7 L - G / D / S / K6 ×1 810.0 lm |
| 管理番号     | K0167253 ( 0 ) DB 1                 |
| BZ分類     | BZ3                                 |

| 器具効率         |                 | 56 %            | 反射率  | 天井                | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------------|-----------------|-----------------|------|-------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|              |                 |                 |      | 壁                 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|              |                 |                 |      | 床                 | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
| 上方光束<br>下方光束 |                 | 56 %            | 室指数  | 照明率 ( X0.01 ) ZCM |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率          |                 | 良<br>中<br>否     | 0.67 | 0.6               | 35   | 29 | 25 | 23 | 35   | 29 | 25 | 23 | 33   | 28 | 25 | 22 | 32   | 28 | 25 | 22 | 21  |
|              |                 |                 | 0.63 | 0.8               | 41   | 35 | 32 | 29 | 40   | 35 | 31 | 29 | 39   | 34 | 31 | 29 | 38   | 34 | 31 | 29 | 28  |
|              |                 |                 | 0.56 | 1.0               | 45   | 40 | 36 | 33 | 44   | 39 | 36 | 33 | 42   | 38 | 35 | 33 | 41   | 38 | 35 | 33 | 32  |
|              |                 |                 |      | 1.25              | 48   | 43 | 40 | 37 | 47   | 43 | 40 | 37 | 45   | 42 | 39 | 37 | 44   | 41 | 39 | 37 | 35  |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5  | 50                | 46   | 43 | 40 | 49 | 45   | 42 | 40 | 47 | 44   | 42 | 40 | 46 | 43   | 41 | 39 | 38 |     |
| 等価発光面積       |                 | cm <sup>2</sup> | 2.0  | 52                | 49   | 46 | 44 | 52 | 49   | 46 | 44 | 50 | 48   | 45 | 44 | 49 | 47   | 45 | 43 | 42 |     |
| 取付<br>高さ     | 器具間隔最大限         |                 | 2.5  | 54                | 51   | 49 | 47 | 53 | 51   | 49 | 47 | 52 | 50   | 48 | 46 | 50 | 49   | 47 | 46 | 44 |     |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0  | 55                | 53   | 51 | 49 | 54 | 52   | 50 | 49 | 53 | 51   | 49 | 48 | 51 | 50   | 49 | 47 | 46 |     |
| H m          | 1.25 H m        | 1.25 H m        | 4.0  | 56                | 55   | 53 | 51 | 56 | 54   | 52 | 51 | 54 | 53   | 52 | 50 | 53 | 52   | 51 | 50 | 48 |     |
|              |                 |                 | 5.0  | 57                | 56   | 54 | 53 | 57 | 55   | 54 | 53 | 55 | 54   | 53 | 52 | 54 | 53   | 52 | 51 | 50 |     |
|              |                 |                 | 7.0  | 58                | 57   | 56 | 55 | 57 | 56   | 55 | 55 | 56 | 55   | 54 | 54 | 55 | 54   | 53 | 53 | 51 |     |
|              |                 |                 | 10.0 | 59                | 58   | 57 | 57 | 58 | 57   | 57 | 56 | 57 | 56   | 56 | 55 | 56 | 55   | 55 | 54 | 53 |     |

