

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 3 WK
光源	LDA4 L - G/ K4 ×1 485.0 lm
管理番号	K0178356 (0) DB 1
B Z 分類	BZ3

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	46	38	33	29	45	38	33	29	44	37	32	29	42	36	32	29	28
			0.63	0.8	53	46	41	38	53	46	41	38	51	45	41	38	49	44	40	37	36
			0.56	1.0	58	52	47	44	57	51	47	43	55	50	46	43	54	49	46	43	41
				1.25	62	57	52	49	61	56	52	49	59	55	51	48	58	54	51	48	46
下方投影面積		cm ²		1.5	65	60	56	53	64	59	55	52	62	58	55	52	60	57	54	51	50
			等価発光面積	cm ²	2.0	68	64	61	58	67	63	60	58	65	62	59	57	64	61	58	56
取付 高さ	器具間隔最大限			2.5	71	67	64	61	70	66	63	61	68	65	62	60	66	63	61	60	58
	横方向 (A) 縦方向 (B)			3.0	72	69	66	64	71	68	66	64	69	67	65	63	67	65	64	62	60
H m	1.27 H m 1.27 H m			4.0	74	71	69	67	73	71	69	67	71	69	67	66	69	68	66	65	63
				5.0	75	73	71	69	74	72	70	69	72	71	69	68	70	69	68	67	65
				7.0	76	75	73	72	75	74	73	71	73	72	71	70	72	71	70	69	67
				10.0	77	76	75	74	76	75	74	73	74	74	73	72	73	72	71	71	69

