

| | |
|----------|--------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XL585PFU |
| 光源 | LED4000_85_10670 ×1 10670.0 1m |
| 管理番号 | K0130721(7)DB1 |
| BZ分類 | BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|---------|---------------|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 100% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.81 | 0.6 | 57 | 44 | 37 | 31 | 55 | 44 | 36 | 31 | 53 | 43 | 36 | 31 | 51 | 42 | 36 | 31 | 29 |
| | 中 | 0.77 | 0.8 | 67 | 55 | 47 | 42 | 65 | 55 | 47 | 42 | 63 | 53 | 46 | 41 | 60 | 52 | 46 | 41 | 39 |
| | 否 | 0.68 | 1.0 | 73 | 63 | 55 | 49 | 72 | 62 | 55 | 49 | 69 | 60 | 54 | 49 | 66 | 59 | 53 | 49 | 46 |
| | | | 1.25 | 79 | 70 | 63 | 57 | 78 | 69 | 62 | 57 | 75 | 67 | 61 | 56 | 72 | 65 | 60 | 56 | 54 |
| 下方投影面積 | | | 1.5 | 84 | 75 | 68 | 63 | 82 | 74 | 67 | 62 | 79 | 72 | 66 | 62 | 76 | 70 | 65 | 61 | 59 |
| | | | 2.0 | 89 | 82 | 76 | 71 | 88 | 81 | 75 | 71 | 85 | 79 | 74 | 70 | 82 | 77 | 73 | 69 | 67 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 93 | 87 | 81 | 77 | 91 | 85 | 81 | 76 | 88 | 83 | 79 | 75 | 85 | 81 | 78 | 74 | 72 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 95 | 90 | 85 | 81 | 94 | 89 | 84 | 80 | 91 | 86 | 83 | 79 | 88 | 84 | 81 | 78 | 76 |
| 1.5m | 1.98m | 1.98m | 4.0 | 98 | 94 | 90 | 87 | 97 | 93 | 89 | 86 | 94 | 91 | 88 | 85 | 91 | 89 | 86 | 84 | |
| 2 | 2.6 | 2.6 | 5.0 | 100 | 97 | 93 | 90 | 99 | 95 | 92 | 90 | 96 | 93 | 91 | 88 | 93 | 91 | 89 | 87 | |
| 2.5 | 3.23 | 3.24 | 7.0 | 102 | 100 | 97 | 95 | 101 | 99 | 96 | 94 | 98 | 96 | 94 | 93 | 96 | 94 | 93 | 91 | |
| 3 | 3.84 | 3.85 | 10.0 | 104 | 102 | 100 | 99 | 103 | 101 | 99 | 98 | 100 | 99 | 97 | 96 | 98 | 96 | 95 | 94 | |

