

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 5 WK
光源	LDA4 L - H - E17 / E / S / W/ 2 ×1 440.0 l m
管理番号	K0164471 (0) DD 1
B Z 分類	BZ4

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	42	34	29	25	41	34	29	25	40	33	28	25	38	32	28	25	23
			0.63	0.8	50	42	37	33	49	42	37	33	47	41	36	33	45	40	36	33	31
			0.56	1.0	55	48	43	39	54	47	43	39	52	46	42	39	50	45	41	38	37
				1.25	59	53	48	45	58	52	48	44	56	51	47	44	54	50	47	44	42
下方投影面積		c m ²		1.5	62	56	52	49	61	56	52	48	59	54	51	48	57	53	50	47	46
			等価発光面積	c m ²	2.0	66	61	57	54	65	60	57	54	63	59	56	53	61	58	55	53
取付 高さ	器具間隔最大限			2.5	68	64	61	58	67	63	60	58	65	62	59	57	63	60	58	56	55
	横方向 (A) 縦方向 (B)			3.0	70	66	63	61	68	65	63	60	67	64	62	60	65	62	61	59	57
H m	1.41 H m	1.41 H m		4.0	71	69	66	64	70	68	66	64	69	67	65	63	67	65	63	62	60
				5.0	73	70	69	67	72	70	68	66	70	68	67	65	68	67	65	64	62
				7.0	74	72	71	69	73	72	70	69	71	70	69	68	70	68	68	67	65
				10.0	75	74	73	72	74	73	72	71	72	71	71	70	71	70	69	69	66

