

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 6 WK
光源	LDA4 L - G - E17 / S / K4 ×1 440.0 lm
管理番号	K0164472 (0) DD 1
BZ分類	BZ5 / 1.8 / BZ4

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	39	30	25	21	38	30	24	21	36	29	24	20	35	28	24	20	19
			0.63	0.8	47	38	33	29	46	38	33	29	44	37	32	28	42	36	32	28	27
			0.56	1.0	52	44	39	35	51	44	38	34	49	42	38	34	47	41	37	34	32
				1.25	56	49	44	40	55	49	44	40	53	47	43	40	51	46	43	40	38
下方投影面積		cm ²		1.5	59	53	48	45	58	52	48	44	56	51	47	44	54	50	46	44	42
				2.0	63	58	54	51	62	58	54	50	60	56	53	50	58	55	52	49	48
等価発光面積		cm ²		2.5	66	62	58	55	65	61	57	55	63	59	56	54	61	58	55	53	51
				3.0	68	64	61	58	66	63	60	57	64	62	59	57	62	60	58	56	54
H _m	1.57H _m	1.57H _m		4.0	70	67	64	62	69	66	64	61	67	64	62	60	65	63	61	60	58
				5.0	71	69	66	64	70	68	66	64	68	66	64	63	66	65	63	62	60
				7.0	72	71	69	68	72	70	68	67	70	68	67	66	68	67	66	65	63
				10.0	74	72	71	70	73	72	70	69	71	70	69	68	69	68	68	67	65

