

屋内照明器具特性	
品番 (品名)	NND2 6 0 4 1 K
光源	LEDRED_90_18 ×1 18.0 l m
管理番号	K0146260 (0) DD 1
BZ分類	BZ3 / 3.5 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		9 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		9 1 %																							
保守率		良 中 否	0 . 8 8	0 . 6	6 3	5 3	4 6	4 2	6 2	5 2	4 6	4 2	5 9	5 1	4 5	4 1	5 6	4 9	4 4	4 0	3 8				
			0 . 8 6	0 . 8	7 2	6 3	5 6	5 1	7 0	6 2	5 5	5 1	6 7	5 9	5 4	5 0	6 4	5 8	5 3	4 9	4 7				
			0 . 8 1	1 . 0	7 8	6 9	6 3	5 8	7 6	6 8	6 2	5 8	7 2	6 6	6 0	5 6	6 9	6 3	5 9	5 5	5 2				
				1 . 2 5	8 3	7 5	6 9	6 5	8 1	7 4	6 8	6 4	7 7	7 1	6 6	6 2	7 3	6 8	6 4	6 1	5 8				
下方投影面積		c m ²	1 . 5	8 6	7 9	7 4	6 9	8 4	7 8	7 2	6 8	8 0	7 5	7 0	6 7	7 6	7 2	6 8	6 5	6 2					
			2 . 0	9 1	8 5	8 0	7 6	8 9	8 3	7 9	7 5	8 4	8 0	7 6	7 3	8 1	7 7	7 4	7 1	6 7					
等価発光面積		c m ²	2 . 5	9 4	8 8	8 4	8 0	9 1	8 7	8 3	7 9	8 7	8 3	8 0	7 7	8 3	8 0	7 7	7 5	7 1					
			3 . 0	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 2	8 9	8 6	8 3	8 0	8 5	8 2	8 0	7 8	7 3					
H m	0 . 7 6 H m	1 . 1 8 H m	4 . 0	9 8	9 4	9 1	8 8	9 6	9 2	8 9	8 7	9 1	8 9	8 6	8 4	8 7	8 5	8 3	8 1	7 7					
			5 . 0	9 9	9 6	9 4	9 1	9 7	9 4	9 2	9 0	9 3	9 1	8 9	8 7	8 9	8 7	8 5	8 4	7 9					
			7 . 0	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 5	9 3	9 1	9 0	9 1	8 9	8 8	8 7	8 2					
			1 0 . 0	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 6	9 5	9 4	9 2	9 2	9 1	9 0	8 9	8 4					

