

屋内照明器具特性

品番 (品名)	NNN61511WZ				
光源	LDA4L-G/K4	x1	485.0lm		
管理番号	K0178348(0)DB1				
BZ分類	BZ3				

器具効率	59%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		59%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	37	31	27	25	37	31	27	25	36	30	27	24	34	30	27	24	23	
	中	0.63	0.8	43	38	34	31	42	37	34	31	41	36	33	31	40	36	33	31	29	
	否	0.56	1.0	47	42	38	35	46	41	38	35	45	40	37	35	43	40	37	35	34	
			1.25	50	45	42	39	49	45	42	39	48	44	41	39	46	43	41	39	37	
下方投影面積			cm ²	1.5	52	48	45	42	51	47	44	42	50	46	44	42	48	46	43	41	40
	等価発光面積		cm ²	2.0	55	51	49	46	54	51	48	46	52	50	48	46	51	49	47	45	44
取付高さ	器具間隔最大限			2.5	56	54	51	49	56	53	51	49	54	52	50	48	53	51	49	48	46
	横方向 (A)	縦方向 (B)		3.0	58	55	53	51	57	55	53	51	55	53	52	50	54	52	51	50	48
Hm	1.15Hm	1.15Hm		4.0	59	57	55	54	58	56	55	53	57	55	54	53	55	54	53	52	50
				5.0	60	58	57	56	59	58	56	55	58	56	55	54	56	55	54	53	52
				7.0	61	60	59	58	60	59	58	57	59	58	57	56	57	57	56	55	54
				10.0	62	61	60	59	61	60	59	59	59	59	58	58	58	58	57	57	55

