

# 屋内照明器具特性

品番 (品名)	NNN61513WK				
光源	LDA7L-G/D/S/K6	x1	810.0lm		
管理番号	K0167254(0)DB1				
BZ分類	BZ3				

器具効率	65%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%																			
下方光束	65%																			
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	41	34	30	27	41	34	30	27	39	33	30	27	38	33	29	27	26
	中	0.63	0.8	48	42	37	34	47	41	37	34	46	41	37	34	44	40	36	34	33
	否	0.56	1.0	52	47	43	39	51	46	42	39	50	45	42	39	48	44	41	39	38
			1.25	56	51	47	44	55	50	47	44	53	49	46	44	52	48	46	43	42
下方投影面積	cm <sup>2</sup>		1.5	58	54	50	47	57	53	50	47	56	52	49	47	54	51	48	46	45
等価発光面積	cm <sup>2</sup>		2.0	61	58	55	52	60	57	54	52	59	56	53	51	57	55	53	51	49
取付高さ	器具間隔最大限		2.5	63	60	57	55	62	59	57	55	61	58	56	54	59	57	55	54	52
	横方向 (A)	縦方向 (B)	3.0	64	62	59	57	64	61	59	57	62	60	58	56	60	59	57	56	54
Hm	1.25Hm	1.25Hm	4.0	66	64	62	60	65	63	61	60	63	62	60	59	62	61	59	58	57
			5.0	67	65	64	62	66	64	63	62	64	63	62	61	63	62	61	60	58
			7.0	68	67	66	64	67	66	65	64	66	65	64	63	64	63	62	62	60
			10.0	69	68	67	66	68	67	66	66	66	66	65	64	65	64	64	63	61

