

屋内照明器具特性	
品番 (品名)	XLX860SEVJ
光源	LED3500_85_5800 ×1 5800.0 lm
管理番号	K0133843 (1) DR 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	5 6	4 3	3 5	3 0	5 4	4 2	3 5	2 9	5 2	4 1	3 4	2 9	5 0	4 0	3 4	2 9	2 7	
			0 . 7 7	0 . 8	6 6	5 4	4 6	4 0	6 4	5 3	4 5	4 0	6 1	5 1	4 5	3 9	5 9	5 0	4 4	3 9	3 7	
			1 . 0	7 2	6 1	5 3	4 7	7 0	6 0	5 3	4 7	6 7	5 8	5 2	4 6	6 5	5 7	5 1	4 6	4 4		
			0 . 6 8	1 . 2 5	7 8	6 8	6 0	5 4	7 6	6 7	6 0	5 4	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 3	5 1	
下方投影面積 等価発光面積		c m ²	1 . 5	8 2	7 3	6 6	6 0	8 1	7 2	6 5	6 0	7 7	7 0	6 4	5 9	7 4	6 8	6 3	5 9	5 6		
			2 . 0	8 8	8 0	7 4	6 9	8 6	7 9	7 3	6 8	8 3	7 7	7 2	6 7	8 0	7 5	7 1	6 7	6 4		
取付 高さ	器具間隔最大限		2 . 5	9 2	8 5	7 9	7 5	9 0	8 4	7 9	7 4	8 7	8 2	7 7	7 3	8 4	7 9	7 6	7 2	6 9		
	横方向 (A)	縦方向 (B)	3 . 0	9 4	8 8	8 3	7 9	9 3	8 7	8 3	7 8	9 0	8 5	8 1	7 7	8 7	8 3	7 9	7 6	7 3		
1 . 5 m	2 . 0 8 m	2 . 9 m	4 . 0	9 8	9 3	8 9	8 5	9 6	9 2	8 8	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	7 9		
2	2 . 7 1	3 . 3 1	5 . 0	1 0 0	9 6	9 2	8 9	9 8	9 5	9 1	8 8	9 5	9 2	8 9	8 7	9 2	9 0	8 8	8 5	8 3		
2 . 5	3 . 3 4	3 . 8	7 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7		
3	3 . 9 7	4 . 3 3	1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 0		

