

# 屋内照明器具特性

品番 (品名)	NNN61515WK				
光源	LDA4L-H-E17/S/4 ×1		440.0lm		
管理番号	K0184833(1)DB1				
BZ分類	BZ4/1.4/BZ3/1.8/BZ4				

器具効率	70%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		70%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.2	3.4	2.9	2.5	4.1	3.3	2.8	2.5	3.9	3.3	2.8	2.5	3.8	3.2	2.8	2.5	2.4	
	中	0.63	0.8	4.9	4.2	3.7	3.3	4.8	4.1	3.7	3.3	4.6	4.0	3.6	3.3	4.5	4.0	3.6	3.3	3.1	
	否	0.56	1.0	5.4	4.7	4.2	3.9	5.3	4.7	4.2	3.9	5.1	4.6	4.2	3.8	4.9	4.5	4.1	3.8	3.7	
	下方投影面積	c m <sup>2</sup>		1.25	5.8	5.2	4.8	4.4	5.7	5.1	4.7	4.4	5.5	5.0	4.7	4.4	5.3	4.9	4.6	4.3	4.2
等価発光面積	c m <sup>2</sup>		1.5	6.1	5.5	5.1	4.8	6.0	5.5	5.1	4.8	5.8	5.3	5.0	4.7	5.6	5.2	4.9	4.7	4.5	
	c m <sup>2</sup>		2.0	6.4	6.0	5.6	5.3	6.3	5.9	5.6	5.3	6.1	5.8	5.5	5.2	5.9	5.7	5.4	5.2	5.0	
取付高さ	器具間隔最大限		2.5	6.6	6.3	6.0	5.7	6.5	6.2	5.9	5.7	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	5.4	
	横方向 (A)	縦方向 (B)	3.0	6.8	6.5	6.2	6.0	6.7	6.4	6.1	5.9	6.5	6.3	6.0	5.8	6.3	6.1	5.9	5.8	5.6	
H <sub>m</sub>	1.39H <sub>m</sub>	1.39H <sub>m</sub>	4.0	7.0	6.7	6.5	6.3	6.9	6.7	6.4	6.3	6.7	6.5	6.3	6.2	6.5	6.4	6.2	6.1	5.9	
			5.0	7.1	6.9	6.7	6.5	7.0	6.8	6.6	6.5	6.8	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.1	
			7.0	7.2	7.1	6.9	6.8	7.1	7.0	6.9	6.7	7.0	6.8	6.7	6.6	6.8	6.7	6.6	6.5	6.3	
			10.0	7.3	7.2	7.1	7.0	7.2	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.9	6.8	6.8	6.7	6.5	

