

# 屋内照明器具特性

|         |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNN61515WK                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LDA7L-H-E17/S/6 x1 760.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0184263(1)DB1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/1.1/BZ4                |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|                  |                                      |         |                  |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |    |
|------------------|--------------------------------------|---------|------------------|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|----|----|
| 器具効率             | 73%                                  | 天井      | 80%              |    |     |    | 70% |    |     |    | 50% |    |     |    | 30% |    |     |    | 0% |    |    |
|                  |                                      |         | 反射率              | 壁  | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30 | 10 | 0% |
|                  |                                      |         |                  | 床  | 10% |    |     |    | 10% |    |     |    | 10% |    |     |    | 10% |    |    |    | 0% |
| 上方光束<br>下方光束     | 0%<br>73%                            | 室指数     | 照明率 ( X0.01) ZCM |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |    |    |
| 保守率              | 良<br>中<br>否<br>0.67<br>0.63<br>0.56  | 0.6     | 41               | 32 | 27  | 23 | 40  | 32 | 27  | 23 | 39  | 31 | 26  | 23 | 37  | 31 | 26  | 23 | 21 |    |    |
|                  |                                      | 0.8     | 49               | 41 | 35  | 31 | 48  | 40 | 35  | 31 | 46  | 39 | 34  | 31 | 44  | 38 | 34  | 31 | 29 |    |    |
|                  |                                      | 1.0     | 54               | 46 | 41  | 37 | 53  | 46 | 41  | 37 | 51  | 45 | 40  | 36 | 49  | 44 | 39  | 36 | 35 |    |    |
|                  |                                      | 1.25    | 59               | 52 | 47  | 43 | 57  | 51 | 46  | 42 | 55  | 50 | 45  | 42 | 53  | 49 | 45  | 42 | 40 |    |    |
| 下方投影面積<br>等価発光面積 | c m <sup>2</sup><br>c m <sup>2</sup> | 1.5     | 62               | 55 | 51  | 47 | 61  | 55 | 50  | 47 | 58  | 53 | 49  | 46 | 56  | 52 | 49  | 46 | 44 |    |    |
|                  |                                      | 2.0     | 66               | 61 | 56  | 53 | 65  | 60 | 56  | 53 | 62  | 58 | 55  | 52 | 60  | 57 | 54  | 52 | 50 |    |    |
| 取付<br>高さ         | 器具間隔最大限                              |         | 2.5              | 68 | 64  | 60 | 57  | 67 | 63  | 60 | 57  | 65 | 62  | 59 | 56  | 63 | 60  | 58 | 55 | 54 |    |
|                  | 横方向 (A)<br>縦方向 (B)                   | 3.0     | 70               | 66 | 63  | 60 | 69  | 66 | 63  | 60 | 67  | 64 | 61  | 59 | 65  | 62 | 60  | 58 | 56 |    |    |
| H m              | 1.41H m                              | 1.41H m | 4.0              | 72 | 69  | 67 | 64  | 71 | 69  | 66 | 64  | 69 | 67  | 65 | 63  | 67 | 65  | 64 | 62 | 60 |    |
|                  |                                      |         | 5.0              | 74 | 71  | 69 | 67  | 73 | 70  | 68 | 66  | 71 | 69  | 67 | 65  | 69 | 67  | 66 | 64 | 62 |    |
|                  |                                      |         | 7.0              | 75 | 73  | 72 | 70  | 74 | 73  | 71 | 70  | 72 | 71  | 70 | 68  | 71 | 69  | 68 | 67 | 65 |    |
|                  |                                      |         | 10.0             | 76 | 75  | 74 | 73  | 75 | 74  | 73 | 72  | 74 | 73  | 72 | 71  | 72 | 71  | 70 | 69 | 67 |    |

