

屋内照明器具特性	
品番 (品名)	NNN61515WK
光源	LDA4L-G-E17/S/K4 ×1 440.0lm
管理番号	K0164470(0)DD1
BZ分類	BZ5/0.7/BZ4

器具効率	68%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	68%																																																						
保守率	良 中 否	0.67	0.6	3.9	3.1	2.6	2.2	3.8	3.1	2.6	2.2	3.7	3.0	2.5	2.2	3.5	2.9	2.5	2.2	2.0																																			
		0.63	0.8	4.7	3.9	3.4	3.0	4.6	3.8	3.3	3.0	4.4	3.7	3.3	3.0	4.2	3.7	3.3	2.9	2.8																																			
		0.56	1.0	5.1	4.4	3.9	3.6	5.0	4.4	3.9	3.5	4.8	4.3	3.8	3.5	4.7	4.2	3.8	3.5	3.3																																			
			1.25	5.5	4.9	4.5	4.1	5.4	4.9	4.4	4.1	5.2	4.7	4.4	4.0	5.1	4.6	4.3	4.0	3.9																																			
下方投影面積	c m ²	1.5	5.8	5.3	4.8	4.5	5.7	5.2	4.8	4.5	5.5	5.1	4.7	4.4	5.3	5.0	4.6	4.4	4.2																																				
		2.0	6.2	5.7	5.4	5.1	6.1	5.7	5.3	5.0	5.9	5.5	5.2	5.0	5.7	5.4	5.1	4.9	4.8																																				
取付高さ	器具間隔最大限		2.5	6.4	6.0	5.7	5.4	6.3	6.0	5.7	5.4	6.1	5.8	5.6	5.3	6.0	5.7	5.5	5.1																																				
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.0	5.7	6.5	6.2	5.9	5.7	6.3	6.0	5.8	5.6	6.1	5.9	5.7	5.4																																				
H m	1.48H m	1.48H m	4.0	6.8	6.5	6.3	6.1	6.7	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.9	5.7																																			
			5.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.5	6.3	6.2	6.1	5.9																																			
			7.0	7.0	6.9	6.7	6.6	7.0	6.8	6.7	6.5	6.8	6.7	6.5	6.4	6.6	6.5	6.4	6.3	6.1																																			
			10.0	7.1	7.0	6.9	6.8	7.1	7.0	6.9	6.8	6.9	6.8	6.7	6.6	6.7	6.7	6.6	6.5	6.3																																			

