

屋内照明器具特性

品番 (品名)	NNN61515WK									
光源	LDA4L-G-E17/S/K4 ×1					440.0lm				
管理番号	K0164470(0)DD1									
BZ分類	BZ5/0.7/BZ4									

器具効率	68%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%																			
下方光束	68%																			
		室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.67	0.6	3.9	3.1	2.6	2.2	3.8	3.1	2.6	2.2	3.7	3.0	2.5	2.2	3.5	2.9	2.5	2.2	2.0
		0.63	0.8	4.7	3.9	3.4	3.0	4.6	3.8	3.3	3.0	4.4	3.7	3.3	3.0	4.2	3.7	3.3	2.9	2.8
		0.56	1.0	5.1	4.4	3.9	3.6	5.0	4.4	3.9	3.5	4.8	4.3	3.8	3.5	4.7	4.2	3.8	3.5	3.3
			1.25	5.5	4.9	4.5	4.1	5.4	4.9	4.4	4.1	5.2	4.7	4.4	4.0	5.1	4.6	4.3	4.0	3.9
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	6.4	6.0	5.7	5.4	6.3	6.0	5.7	5.4	6.1	5.8	5.6	5.3	6.0	5.7	5.5	5.3	5.1
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.0	5.7	6.5	6.2	5.9	5.7	6.3	6.0	5.8	5.6	6.1	5.9	5.7	5.5	5.4
Hm	1.48Hm	1.48Hm	4.0	6.8	6.5	6.3	6.1	6.7	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.9	5.7
			5.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.5	6.3	6.2	6.1	5.9
			7.0	7.0	6.9	6.7	6.6	7.0	6.8	6.7	6.5	6.8	6.7	6.5	6.4	6.6	6.5	6.4	6.3	6.1
			10.0	7.1	7.0	6.9	6.8	7.1	7.0	6.9	6.8	6.9	6.8	6.7	6.6	6.7	6.7	6.6	6.5	6.3

