

屋内照明器具特性

品番 (品名)	NNN61515WK									
光源	LDA6L-H-E17 ×1					440.0lm				
管理番号	K0137751(2)DB1									
BZ分類	BZ5/0.7/BZ4									

器具効率	80%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 80%	室指数	照明率 (X0.01)																ZCM			
保守率	良	0.67	0.6	46	36	30	26	45	36	30	26	43	35	29	26	41	34	29	25	24	
	中	0.63	0.8	54	45	39	35	53	45	39	35	51	44	38	34	49	43	38	34	33	
	否	0.56	1.0	60	52	46	41	59	51	45	41	56	50	45	41	54	48	44	41	39	
			1.25	65	57	52	47	63	57	51	47	61	55	51	47	59	54	50	47	45	
下方投影面積			1.5	68	61	56	52	67	61	56	52	64	59	55	51	62	58	54	51	49	
	等価発光面積		2.0	72	67	62	59	71	66	62	58	69	64	61	58	67	63	60	57	55	
取付高さ	器具間隔最大限		2.5	75	70	66	63	74	70	66	63	72	68	65	62	69	66	64	61	59	
	横方向 (A)	縦方向 (B)	3.0	77	73	69	66	76	72	69	66	73	70	68	65	71	69	66	64	62	
Hm	1.34Hm	1.34Hm	4.0	79	76	73	71	78	75	73	70	76	73	71	69	74	72	70	68	66	
			5.0	81	78	76	74	80	77	75	73	77	75	73	72	75	74	72	71	69	
			7.0	82	80	79	77	81	79	78	76	79	78	76	75	77	76	75	74	71	
			10.0	83	82	81	80	82	81	80	79	80	79	78	77	79	78	77	76	74	

