

屋内照明器具特性

品番 (品名)	NNN61515WK	
光源	LDA6L-E17/D ×1	370.0 lm
管理番号	K0137752(2)DB1	
BZ分類	BZ3	

器具効率	67%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		67%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.2	3.4	3.0	2.7	4.1	3.4	3.0	2.7	4.0	3.3	2.9	2.6	3.8	3.3	2.9	2.6	2.5	
	中	0.63	0.8	4.9	4.2	3.8	3.4	4.8	4.2	3.8	3.4	4.6	4.1	3.7	3.4	4.5	4.0	3.7	3.4	3.3	
	否	0.56	1.0	5.3	4.7	4.3	4.0	5.2	4.7	4.3	4.0	5.1	4.6	4.2	3.9	4.9	4.5	4.2	3.9	3.8	
			1.25	5.7	5.2	4.8	4.5	5.6	5.1	4.7	4.4	5.4	5.0	4.7	4.4	5.3	4.9	4.6	4.4	4.2	
下方投影面積	cm ²		1.5	5.9	5.5	5.1	4.8	5.8	5.4	5.1	4.8	5.7	5.3	5.0	4.7	5.5	5.2	4.9	4.7	4.6	
	等価発光面積		2.0	6.3	5.9	5.6	5.3	6.2	5.8	5.5	5.3	6.0	5.7	5.4	5.2	5.8	5.6	5.3	5.2	5.0	
取付高さ	器具間隔最大限		2.5	6.4	6.1	5.8	5.6	6.4	6.1	5.8	5.6	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.3	
	横方向 (A)	縦方向 (B)	3.0	6.6	6.3	6.1	5.8	6.5	6.2	6.0	5.8	6.3	6.1	5.9	5.7	6.1	6.0	5.8	5.7	5.5	
Hm	1.40Hm	1.40Hm	4.0	6.7	6.5	6.3	6.1	6.7	6.4	6.3	6.1	6.5	6.3	6.2	6.0	6.3	6.2	6.0	5.9	5.8	
			5.0	6.8	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	5.9	
			7.0	7.0	6.8	6.7	6.6	6.9	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.5	6.5	6.4	6.3	6.1	
			10.0	7.0	6.9	6.9	6.8	7.0	6.9	6.8	6.7	6.8	6.7	6.6	6.6	6.6	6.6	6.6	6.5	6.3	

