

屋内照明器具特性	
品番 (品名)	NNN61515WK
光源	LDA7L-G-E17/K60E/S/W/2 x1 760.0 1m
管理番号	K0157872(0)DB1
BZ分類	BZ5

器具効率	69%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	69%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	3.8	2.9	2.4	2.0	3.7	2.9	2.3	2.0	3.5	2.8	2.3	2.0	3.4	2.7	2.3	1.9	1.8
	中	0.63	0.8	4.5	3.7	3.2	2.8	4.4	3.7	3.1	2.7	4.2	3.6	3.1	2.7	4.1	3.5	3.0	2.7	2.6
	否	0.56	1.0	5.0	4.3	3.7	3.3	4.9	4.2	3.7	3.3	4.7	4.1	3.6	3.3	4.5	4.0	3.6	3.3	3.1
			1.25	5.5	4.8	4.3	3.9	5.4	4.7	4.3	3.9	5.2	4.6	4.2	3.8	5.0	4.5	4.1	3.8	3.6
下方投影面積		cm <sup>2</sup>	1.5	5.8	5.2	4.7	4.3	5.7	5.1	4.6	4.3	5.5	5.0	4.6	4.2	5.3	4.8	4.5	4.2	4.0
等価発光面積		cm <sup>2</sup>	2.0	6.2	5.7	5.3	4.9	6.1	5.6	5.2	4.9	5.9	5.5	5.1	4.8	5.7	5.3	5.0	4.8	4.6
取付高さ	器具間隔最大限		2.5	6.4	6.0	5.6	5.3	6.3	5.9	5.6	5.3	6.1	5.8	5.5	5.2	5.9	5.6	5.4	5.2	5.0
	横方向 (A)	縦方向 (B)	3.0	6.6	6.2	5.9	5.6	6.5	6.2	5.9	5.6	6.3	6.0	5.7	5.5	6.1	5.9	5.6	5.4	5.3
Hm	1.59Hm	1.59Hm	4.0	6.8	6.5	6.3	6.0	6.7	6.5	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.8	5.6
			5.0	7.0	6.7	6.5	6.3	6.9	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.5	6.3	6.2	6.0	5.9
			7.0	7.1	6.9	6.8	6.6	7.0	6.9	6.7	6.6	6.8	6.7	6.6	6.4	6.7	6.5	6.4	6.3	6.1
			10.0	7.2	7.1	7.0	6.9	7.1	7.0	6.9	6.8	7.0	6.9	6.8	6.7	6.8	6.7	6.6	6.5	6.3

