

屋内照明器具特性	
品番 (品名)	NNN61515WK
光源	LDA4L-H-E17/E/S/W/2×1 440.0lm
管理番号	K0164471(0)DD1
BZ分類	BZ4

器具効率		72 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	42	34	29	25	41	34	29	25	40	33	28	25	38	32	28	25	23				
			0.63	0.8	50	42	37	33	49	42	37	33	47	41	36	33	45	40	36	33	31				
			0.56	1.0	55	48	43	39	54	47	43	39	52	46	42	39	50	45	41	38	37				
				1.25	59	53	48	45	58	52	48	44	56	51	47	44	54	50	47	44	42				
下方投影面積		cm ²		1.5	62	56	52	49	61	56	52	48	59	54	51	48	57	53	50	47	46				
等価発光面積			cm ²	2.0	66	61	57	54	65	60	57	54	63	59	56	53	61	58	55	53	51				
取付高さ	器具間隔最大限			2.5	68	64	61	58	67	63	60	58	65	62	59	57	63	60	58	56	55				
	横方向 (A)			縦方向 (B)		3.0	70	66	63	61	68	65	63	60	67	64	62	60	65	62	61	59	57		
H m	1.41 H m	1.41 H m			4.0	71	69	66	64	70	68	66	64	69	67	65	63	67	65	63	62	60			
				5.0	73	70	69	67	72	70	68	66	70	68	67	65	68	67	65	64	62				
				7.0	74	72	71	69	73	72	70	69	71	70	69	68	70	68	68	67	65				
				10.0	75	74	73	72	74	73	72	71	72	71	71	70	71	70	69	69	66				

