

屋内照明器具特性

品番 (品名)	NNN61516WK															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0184834(1)DB1															
BZ分類	BZ5/0.7/BZ4															

器具効率	71%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 71%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	41	33	27	24	40	32	27	24	39	32	27	24	37	31	27	23	22		
		0.8	49	41	36	32	48	41	36	32	46	40	35	32	45	39	35	32	30		
		1.0	54	47	42	38	53	46	42	38	51	45	41	38	49	44	40	37	36		
		1.25	58	52	47	44	57	51	47	43	55	50	46	43	53	49	46	43	41		
下方投影面積 等価発光面積	c m ² c m ²	1.5	61	56	51	48	60	55	51	47	58	54	50	47	56	52	49	47	45		
		2.0	65	60	57	53	64	60	56	53	62	58	55	53	60	57	54	52	50		
取付 高さ	器具間隔最大限		2.5	67	63	60	57	66	63	60	57	64	61	59	56	63	60	58	56	54	
	横方向 (A) H m	縦方向 (B) H m	3.0	69	66	63	60	68	65	62	60	66	63	61	59	64	62	60	58	56	
			4.0	71	68	66	64	70	68	65	63	68	66	64	62	66	65	63	62	60	
			5.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62	
			7.0	74	72	70	69	73	71	70	68	71	70	68	67	69	68	67	66	64	
			10.0	75	73	72	71	74	73	72	71	72	71	70	69	70	69	68	66	64	

