

屋内照明器具特性

品番 (品名)	NNN61516WK									
光源	LDA5L-G-E17/D/S/K4 ×1					440.0 mm				
管理番号	K0184896(1)DB1									
BZ分類	BZ5/1.4/BZ4									

器具効率	72%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		72%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.67	0.6	40	31	25	21	39	31	25	21	37	30	25	21	36	29	25	21	20			
	中	0.63	0.8	48	40	34	30	47	39	34	30	45	38	33	29	43	37	33	29	28			
	否	0.56	1.0	53	45	40	36	52	45	40	36	50	44	39	35	48	43	38	35	34			
			0.56	1.25	58	51	46	42	57	50	45	41	54	49	45	41	52	48	44	41	39		
下方投影面積			cm ²																				
等価発光面積			cm ²																				
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
H _m	1.56H _m	1.56H _m	4.0	72	69	66	64	71	68	65	63	69	66	64	62	67	65	63	61	59			
			5.0	73	71	68	66	72	70	68	66	70	68	66	65	68	67	65	64	62			
			7.0	74	73	71	69	73	72	70	69	72	70	69	68	70	69	68	67	64			
			10.0	76	74	73	72	75	73	72	71	73	72	71	70	71	70	69	69	67			

