

屋内照明器具特性

品番 (品名)	NNN61516WK				
光源	LDA7L-H-E17/S/6 x1 760.0lm				
管理番号	K0184264(1)DB1				
BZ分類	BZ5/4.5/BZ4/6.0/BZ5/8.5/BZ4				

器具効率	73%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		73%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	41	31	26	21	40	31	25	21	38	30	25	21	36	29	25	21	20	
	中	0.63	0.8	48	40	34	30	47	39	34	29	45	38	33	29	43	37	33	29	28	
	否	0.56	1.0	53	45	40	35	52	45	39	35	50	44	39	35	48	43	38	35	33	
			1.25	58	51	45	41	57	50	45	41	55	49	44	41	53	48	44	40	39	
下方投影面積			c m ²	1.5	61	55	50	46	60	54	49	45	58	53	48	45	56	51	48	45	43
			c m ²	2.0	65	60	56	52	64	59	55	52	62	58	54	51	60	56	53	51	49
取付高さ	器具間隔最大限			2.5	68	64	60	56	67	63	59	56	65	61	58	55	63	60	57	55	53
	横方向 (A)	縦方向 (B)		3.0	70	66	63	60	69	65	62	59	67	64	61	58	65	62	60	58	56
H _m	1.43H _m	1.43H _m		4.0	72	69	66	64	71	68	66	63	69	67	64	62	67	65	63	62	60
				5.0	74	71	69	67	73	70	68	66	71	69	67	65	69	67	65	64	62
				7.0	75	73	72	70	74	72	71	69	72	71	69	68	70	69	68	67	65
				10.0	76	75	74	73	75	74	73	72	74	73	72	71	72	71	70	69	67

