

屋内照明器具特性

品番 (品名)	NNN61516WK														
光源	LDA7L-G-E17/K60E/S/W/2 ×1 760.0 1m														
管理番号	K0157873(0)DB1														
BZ分類	BZ6/0.7/BZ5														

器具効率	70%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	0% 70%	室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否 0.67 0.63 0.56	0.6	37	28	22	18	36	27	22	18	34	27	22	18	33	26	21	18	16	
		0.8	45	36	30	26	43	35	30	26	41	34	29	26	40	33	29	25	24	
		1.0	50	42	36	32	48	41	36	31	46	40	35	31	44	39	34	31	29	
		1.25	54	47	42	37	53	46	41	37	51	45	40	37	49	44	40	37	35	
下方投影面積 等価発光面積	c m ² c m ²	1.5	57	51	46	42	56	50	45	41	54	49	44	41	52	47	44	41	39	
		2.0	61	56	52	48	60	55	51	48	58	54	50	47	56	52	49	47	45	
取付 高さ	器具間隔最大限		2.5	64	59	56	52	63	59	55	52	61	57	54	51	59	56	53	51	49
	横方向 (A) 縦方向 (B)	3.0	66	62	58	55	65	61	58	55	63	60	57	54	61	58	56	54	52	
H m	1.63 H m	1.63 H m	4.0	68	65	62	60	67	64	62	59	65	63	60	58	63	61	59	58	56
			5.0	70	67	65	63	69	66	64	62	67	65	63	61	65	63	62	60	58
			7.0	71	69	68	66	70	69	67	65	68	67	65	64	67	65	64	63	61
			10.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	65	63

