

# 屋内照明器具特性

品番 (品名)	NNN61517WK									
光源	LDG4L-G/70/W ×1					430.0 lm				
管理番号	K0158877(0)DB1									
BZ分類	BZ5/1.4/BZ4									

器具効率	73%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		73%		床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良	0.67	0.6	41	32	26	22	40	32	26	22	38	31	26	22	37	30	25	22	21			
	中	0.63	0.8	49	40	35	30	48	40	34	30	46	39	34	30	44	38	33	30	28			
	否	0.56	1.0	54	46	40	36	53	45	40	36	50	44	39	36	48	43	39	36	34			
			0.56	1.25	58	51	46	42	57	51	46	42	55	49	45	41	53	48	44	41	39		
下方投影面積			c m <sup>2</sup>																				
			c m <sup>2</sup>																				
取付高さ	器具間隔最大限																						
	横方向 (A)	縦方向 (B)																					
H m	1.44 H m	1.44 H m																					
			2.5	68	64	60	57	67	63	59	56	65	61	58	56	63	60	57	55	53			
			3.0	70	66	63	60	69	65	62	59	67	63	61	58	65	62	60	58	56			
			4.0	72	69	66	64	71	68	66	63	69	66	64	62	67	65	63	61	60			
			5.0	73	71	69	66	72	70	68	66	70	68	67	65	68	67	65	64	62			
			7.0	75	73	71	70	74	72	71	69	72	71	69	68	70	69	68	67	65			
			10.0	76	75	73	72	75	74	73	72	73	72	71	70	71	71	71	70	69			

