

屋内照明器具特性

品番 (品名)	FYY26250															
光源	LED5000_85_4860 x1 4860.0 1m															
管理番号	K0149129(0)DB1															
BZ分類	BZ6/1.1/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.81	0.6	53	40	31	25	51	39	31	25	49	38	30	25	46	37	30	25	23
		0.77	0.8	63	51	42	36	62	50	42	36	59	48	41	35	56	47	40	35	33
		0.68	1.0	70	58	50	43	68	57	49	43	65	56	49	43	62	54	48	43	40
			1.25	76	66	58	51	75	65	57	51	71	63	56	51	68	61	55	50	48
下方投影面積			1.5	81	71	64	57	79	70	63	57	76	68	62	57	73	66	61	56	53
等価発光面積			2.0	87	79	72	67	85	78	71	66	82	76	70	65	79	73	69	65	62
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	83	77	72	86	80	76	71	83	78	74	71	68
	横方向 (A)	縦方向 (B)	3.0	94	88	82	78	92	86	81	77	89	84	80	76	86	82	78	75	72
1.5m	2.61m	2.09m	4.0	97	92	88	84	96	91	87	83	93	89	85	82	90	87	84	81	78
2	3.42	2.64	5.0	99	95	92	88	98	94	91	88	95	92	89	86	92	89	87	85	82
2.5	4.24	3.21	7.0	102	99	96	93	100	98	95	93	98	95	93	91	95	93	91	89	86
3	5.05	3.8	10.0	104	102	99	97	102	100	98	97	100	98	96	95	97	96	94	93	90

