

屋内照明器具特性	
品番 (品名)	YYY23060
光源	LED3500_70_340 x1 340.0 l m
管理番号	K0178713 (1) DR 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	9 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	91 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.7	0.6	5.4	4.1	3.3	2.8	5.2	4.0	3.3	2.7	4.9	3.8	3.2	2.7	4.6	3.7	3.1	2.6	2.4
	中	0.7	0.8	6.3	5.1	4.3	3.7	6.1	5.0	4.3	3.7	5.7	4.8	4.1	3.6	5.4	4.6	4.0	3.5	3.2
	否	0.68	1.0	7.0	5.9	5.1	4.4	6.8	5.7	5.0	4.4	6.3	5.4	4.8	4.3	5.9	5.2	4.6	4.2	3.8
			1.25	7.6	6.5	5.8	5.2	7.3	6.4	5.7	5.1	6.9	6.1	5.5	5.0	6.5	5.8	5.3	4.8	4.5
下方投影面積		cm ²	1.5	8.0	7.0	6.3	5.7	7.7	6.9	6.2	5.6	7.3	6.5	6.0	5.5	6.9	6.2	5.7	5.3	4.9
等価発光面積		cm ²	2.0	8.5	7.7	7.1	6.5	8.3	7.6	6.9	6.4	7.8	7.2	6.7	6.2	7.4	6.9	6.4	6.0	5.6
取付高さ	器具間隔最大限		2.5	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.2	7.6	7.2	6.8	7.7	7.3	6.9	6.6	6.1
	横方向 (A)	縦方向 (B)	3.0	9.2	8.5	8.0	7.5	8.9	8.3	7.9	7.4	8.4	8.0	7.5	7.2	8.0	7.6	7.3	6.9	6.5
1.5m	1.98 m	1.96 m	4.0	9.5	9.0	8.5	8.1	9.2	8.8	8.4	8.0	8.8	8.4	8.0	7.7	8.3	8.0	7.7	7.5	7.0
2	2.64	2.61	5.0	9.7	9.3	8.9	8.5	9.5	9.1	8.7	8.4	9.0	8.7	8.4	8.1	8.5	8.3	8.0	7.8	7.3
2.5	3.3	3.26	7.0	9.9	9.6	9.3	9.0	9.7	9.4	9.1	8.9	9.2	9.0	8.8	8.5	8.8	8.6	8.4	8.2	7.7
3	3.96	3.91	10.0	10.1	9.9	9.7	9.4	9.9	9.7	9.5	9.3	9.4	9.3	9.1	8.9	9.0	8.9	8.7	8.6	8.1

