

屋内照明器具特性

品番 (品名)	LGB81701														
光源	LED3500_70_447 x1 447.0 lm														
管理番号	K0151935(0)DB1														
BZ分類	BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%				
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				床	10%				10%				10%				10%				0%		
上方光束	28%																						
下方光束	72%																						
室指数	照明率 (X0.01) ZCM																						
保守率	良 中 否	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6			
		0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6		
		0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56		
		0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56		
下方投影面積	c m ²	1.25	70	59	51	45	66	56	49	43	59	51	45	40	52	46	41	37	30				
		1.5	74	64	57	50	70	61	54	48	63	55	49	45	56	50	45	41	34				
等価発光面積	c m ²	2.0	80	71	64	58	76	68	62	56	68	61	56	52	60	55	51	47	40				
		2.5	84	76	70	64	79	72	67	62	71	66	61	57	64	59	55	52	44				
取付高さ	器具間隔最大限		H m	1.46 H m	1.46 H m	3.0	86	79	74	69	82	76	71	66	74	69	64	61	66	62	59	55	47
	4.0	90				84	79	75	85	80	76	72	77	73	69	66	69	66	63	60	51		
H m	1.46 H m	1.46 H m	5.0	92	87	83	79	87	83	79	76	79	76	73	70	71	68	66	64	54			
			7.0	94	91	87	84	90	87	84	81	82	79	77	74	74	72	70	68	58			
			10.0	96	94	91	89	92	90	87	85	84	82	80	78	76	74	73	71	61			

