

屋内照明器具特性

品番 (品名)	XLJ 4 6 1 NENK									
光源	LED5000_85_6560 x1 6560.0 lm									
管理番号	K0141079 (5) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	6 %	室指数	照明率 (X0.01)																ZCM		
下方光束	94 %																				
保守率	良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	50	40	33	28	47	38	32	28	25	
		0.81	0.8	64	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	34	
		0.77	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	48	44	41	
			1.25	77	67	59	53	75	65	58	53	71	63	56	51	67	60	55	50	47	
下方投影面積	c m ²	1.5	81	72	64	59	79	70	63	58	75	67	61	57	71	65	60	55	52		
		2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	67	63	59		
取付高さ	器具間隔最大限		2.5	90	83	77	73	88	82	76	72	84	78	74	70	80	75	71	68	64	
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	90	85	80	76	86	82	77	74	82	78	75	72	68	
1.5m	1.97 m	2.09 m	4.0	96	91	87	83	94	89	85	82	90	86	82	79	86	83	80	77	73	
2	2.6	2.65	5.0	98	94	90	87	96	92	89	85	92	88	86	83	88	85	83	81	76	
2.5	3.24	3.22	7.0	100	97	94	91	98	95	93	90	94	92	89	87	90	88	87	85	80	
3	3.86	3.82	10.0	102	100	98	95	100	98	96	94	96	94	93	91	92	91	90	88	84	

