

屋内照明器具特性

品番 (品名)	NNN61516WK															
光源	LDA4L-H-E17/S/4 x1 440.0lm															
管理番号	K0184834(1)DB1															
BZ分類	BZ5/0.7/BZ4															

器具効率	71%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 71%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	41	33	27	24	40	32	27	24	39	32	27	24	37	31	27	23	22		
		0.8	49	41	36	32	48	41	36	32	46	40	35	32	45	39	35	32	30		
		1.0	54	47	42	38	53	46	42	38	51	45	41	38	49	44	40	37	36		
		1.25	58	52	47	44	57	51	47	43	55	50	46	43	53	49	46	43	41		
下方投影面積 等価発光面積	c m ² c m ²	1.5	61	56	51	48	60	55	51	47	58	54	50	47	56	52	49	47	45		
		2.0	65	60	57	53	64	60	56	53	62	58	55	53	60	57	54	52	50		
取付 高さ	器具間隔最大限		2.5	67	63	60	57	66	63	60	57	64	61	59	56	63	60	58	56	54	
	横方向 (A) 縦方向 (B)	3.0	69	66	63	60	68	65	62	60	66	63	61	59	64	62	60	58	56		
H m	1.47 H m	1.47 H m	4.0	71	68	66	64	70	68	65	63	68	66	64	62	66	65	63	62	60	
			5.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62	
			7.0	74	72	70	69	73	71	70	68	71	70	68	67	69	68	67	66	64	
			10.0	75	73	72	71	74	73	72	71	72	71	70	69	70	70	69	68	66	

