

屋内照明器具特性

品番 (品名)	XLJ 440 NENK									
光源	LED5000_85_3830 x1					3830.0 lm				
管理番号	K0141079 (5) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	6 %	室指数	照明率 (X0.01)																ZCM		
下方光束	94 %																				
保守率	良 中 否	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.8	2.5	
		0.81	0.8	6.4	5.3	4.5	3.9	6.3	5.2	4.4	3.8	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.7	3.4	
		0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.5	6.5	5.6	5.0	4.5	6.2	5.4	4.8	4.4	4.1	
			1.25	7.7	6.7	5.9	5.3	7.5	6.5	5.8	5.3	7.1	6.3	5.6	5.1	6.7	6.0	5.5	5.0	4.7	
下方投影面積	c m ²	1.5	8.1	7.2	6.4	5.9	7.9	7.0	6.3	5.8	7.5	6.7	6.1	5.7	7.1	6.5	6.0	5.5	5.2		
		2.0	8.7	7.9	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.6	7.1	6.7	6.3	5.9		
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.3	8.8	8.2	7.6	7.2	8.4	7.8	7.4	7.0	8.0	7.5	7.1	6.8	6.4	
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.1	7.7	9.0	8.5	8.0	7.6	8.6	8.2	7.7	7.4	8.2	7.8	7.5	7.2	6.8	
1.5m	1.97 m	2.09 m	4.0	9.6	9.1	8.7	8.3	9.4	8.9	8.5	8.2	9.0	8.6	8.2	7.9	8.6	8.3	8.0	7.7	7.3	
2	2.6	2.65	5.0	9.8	9.4	9.0	8.7	9.6	9.2	8.9	8.5	9.2	8.8	8.6	8.3	8.8	8.5	8.3	8.1	7.6	
2.5	3.24	3.22	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.3	9.0	9.4	9.2	8.9	8.7	9.0	8.8	8.7	8.5	8.0	
3	3.86	3.82	10.0	10.2	10.0	9.8	9.5	10.0	9.8	9.6	9.4	9.6	9.4	9.3	9.1	9.2	9.1	9.0	8.8	8.4	

